

雙層塑膠高速吹袋機

HDPE / LDPE / LLDPE

Two Layer High Speed
Plastic Inflation Machine

KMTL-55



KANG CHYAU



雙層塑膠高速吹袋機 HDPE / LDPE / LLDPE Two Layer High Speed Plastic Inflation Machine

KMTL-55 SPECIFICATION 產品系列與規格表

MODEL 機型	KMTL-55
SUITABLE MATERIAL 適用原料	HDPE / LDPE / LLDPE
FILM THICKNESS 膜厚	0.025~0.15 mm
FILM WIDTH RANGE 膜寬	1400 mm
FILM OUTPUT 最大膠膜產量	20~150 kgs / hr
EXTRUDER UNIT 主機部份	
SCREW DIAMETER / TYPE 螺桿直徑 / 型號	Ø 55 mm × 2
SCREW L / D RATIO 螺桿長徑比	28 : 1
HEATING CAPACITY 電熱量	24 kw
AUTO THERMO CONTROL 溫控點	6 zone
BARREL COOLING FAN 螺桿冷卻風扇	1/8 hp × 4
DRIVING MOTOR 主驅動馬達	AC 30 hp + INVERTER
DIE UNIT 模頭部份	
DIE DIAMETER 模頭直徑	Ø 350 mm
AIR RING DIAMETER 風環直徑	Ø 400 mm
HEATING CAPACITY 電熱量	18.4 kw
AUTO THERMO CONTROL 溫控點	3 zone
COOLING BLOWER 冷卻風車	7 1/2 hp
TAKE-UP UNIT 引取部份	
TAKE - UP ROLLER 引取輪寬	1500 mm
EFFECTIVE WIDTH 有效引取輪寬	1400 mm
TAKE - UP MOTOR 引取馬達	AC 2 hp
TAKE - UP SPEED 引取速度	45 m / min
ELEVATING MOTOR 昇降馬達	
WINDING UNIT 捲取部份	
ROLLER WIDTH 捲取輪寬	1500 mm
WINDING WIDTH 有效捲取寬度	1400 mm
WINDING MOTOR 捲取馬達	DC 1 hp
MACHINE DIMENSION 機器尺寸	500 × 500 × 800 cm

REMARK : The above machine specification and production range can be changed without any notice due to kind of different application.
型錄上之圖片及係數只備參考其尺寸，規格，樣式會因客人所訂購的配件不同而有所改變

康喬工業有限公司 KANG CHYAU INDUSTRY CO., LTD.

247 新北市蘆洲區復興路 227 巷 28 弄 2-10 號
No. 2-10, Aly. 28, Ln. 227, Fuxing Rd., Luzhou Dist., New Taipei City 247, Taiwan
Mail Box: P. O. Box 5-56, Luzhou Dist., New Taipei City 247, Taiwan
Tel: +886-2-22856880~1 Fax: +886-2-22856883
E-mail: kang.chyou@msa.hinet.net Internet: www.kangchyou.com.tw

