

雙層塑膠高速吹袋機

HDPE / LDPE / LLDPE

Two Layer High Speed
Plastic Inflation Machine

KMTL-65



KANG CHYAU



雙層塑膠高速吹袋機 HDPE / LDPE / LLDPE Two Layer High Speed Plastic Inflation Machine

KMTL-65 SPECIFICATION 產品系列與規格表

| MODEL 機型 | KMTL-65 |
|---------------------------------|---------------------|
| SUITABLE MATERIAL 適用原料 | HDPE / LDPE / LLDPE |
| FILM THICKNESS 膜厚 | 0.03~0.15 mm |
| FILM WIDTH RANGE 膜寬 | 2000 mm |
| FILM OUTPUT 最大膠膜產量 | 60~250 kgs / hr |
| EXTRUDER UNIT 主機部份 | |
| SCREW DIAMETER / TYPE 螺桿直徑 / 型號 | Ø 65 mm x 2 |
| SCREW L / D RATIO 螺桿長徑比 | 28 : 1 |
| HEATING CAPACITY 電熱量 | 29.4 kw |
| AUTO THERMO CONTROL 溫控點 | 8 zone |
| BARREL COOLING FAN 螺桿冷卻風扇 | 1/8 hp X 8 |
| DRIVING MOTOR 主驅動馬達 | AC 50 hp + INVERTER |
| DIE UNIT 模頭部份 | |
| DIE DIAMETER 模頭直徑 | Ø 500 mm |
| AIR RING DIAMETER 風環直徑 | Ø 550 mm |
| HEATING CAPACITY 電熱量 | 24 kw |
| AUTO THERMO CONTROL 溫控點 | 3 zone |
| COOLING BLOWER 冷卻風車 | 10 hp |
| TAKE-UP UNIT 引取部份 | |
| TAKE - UP ROLLER 引取輪寬 | 2200 mm |
| EFFECTIVE WIDTH 有效引取輪寬 | 2000 mm |
| TAKE - UP MOTOR 引取馬達 | AC 3 hp |
| TAKE - UP SPEED 引取速度 | 40 m / min |
| ELEVATING MOTOR 昇降馬達 | |
| WINDING UNIT 捲取部份 | |
| ROLLER WIDTH 捲取輪寬 | 2200 mm |
| WINDING WIDTH 有效捲取寬度 | 2000 mm |
| WINDING MOTOR 捲取馬達 | DC 2 hp |
| MACHINE DIMENSION 機器尺寸 | |

REMARK : The above machine specification and production range can be changed without any notice due to kind of different application.
型錄上之圖片及係數只備參考其尺寸，規格，樣式會因客人所訂購的配件不同而有所改變

康喬工業有限公司 KANG CHYAU INDUSTRY CO., LTD.

247 新北市蘆洲區復興路 227 巷 28 弄 2-10 號
No. 2-10, Aly. 28, Ln. 227, Fuxing Rd., Luzhou Dist., New Taipei City 247, Taiwan
Mail Box: P. O. Box 5-56, Luzhou Dist., New Taipei City 247, Taiwan
Tel: +886-2-22856880~1 Fax: +886-2-22856883
E-mail: kang.chyou@msa.hinet.net Internet: www.kangchyou.com.tw

