

雙層塑膠高速吹袋機

HDPE / LDPE / LLDPE

Two Layer High Speed
Plastic Inflation Machine

KMTL-40/45



KANG CHYAU



雙層塑膠高速吹袋機 HDPE / LDPE / LLDPE Two Layer High Speed Plastic Inflation Machine

KMTL-40/45 SPECIFICATION 產品系列與規格表

MODEL 機型	KMTL-40	KMTL-45
SUITABLE MATERIAL 適用原料	HDPE / LDPE / LLDPE	HDPE / LDPE / LLDPE
FILM THICKNESS 膜厚	0.010~0.15 mm	0.010~0.15 mm
FILM WIDTH RANGE 膜寬	800 mm	900 mm
FILM OUTPUT 最大膠膜產量	15~70 kgs / hr	20~90 kgs / hr
EXTRUDER UNIT 主機部份		
SCREW DIAMETER / TYPE 螺桿直徑 / 型號	Ø 40 mm × 2	Ø 45 mm × 2
SCREW L / D RATIO 螺桿長徑比	26 : 1	26 : 1
HEATING CAPACITY 電熱量	13.2 kw	17.2 kw
AUTO THERMO CONTROL 溫控點	6 zone	2 zone
BARREL COOLING FAN 螺桿冷卻風扇	1/8 hp × 2	1/8 hp × 4
DRIVING MOTOR 主驅動馬達	AC 20 hp + INVERTER	AC 20 hp + INVERTER
DIE UNIT 模頭部份		
DIE DIAMETER 模頭直徑	Ø 80 / 175 mm	Ø 100 / 200 mm
AIR RING DIAMETER 風環直徑	Ø 120 / 200 mm	Ø 150 / 250 mm
HEATING CAPACITY 電熱量	6.2 kw	10 kw
AUTO THERMO CONTROL 溫控點	2 zone	3 zone
COOLING BLOWER 冷卻風車	3 hp	5 hp
TAKE-UP UNIT 引取部份		
TAKE - UP ROLLER 引取輪寬	1000 mm	1100 mm
EFFECTIVE WIDTH 有效引取輪寬	900 mm	1000 mm
TAKE - UP MOTOR 引取馬達	AC 1/2 hp	AC 1/2 hp
TAKE - UP SPEED 引取速度	70 m / min	70 m / min
ELEVATING MOTOR 昇降馬達	AC 1/2 hp	AC 1/2 hp
WINDING UNIT 捲取部份		
ROLLER WIDTH 捲取輪寬	1000 mm	1100 mm
WINDING WIDTH 有效捲取寬度	900 mm	1000 mm
WINDING MOTOR 捲取馬達	DC 1 hp	DC 1 hp
MACHINE DIMENSION 機器尺寸	450 × 200 × 400 cm	470 × 220 × 450 cm

REMARK : The above machine specification and production range can be changed without any notice due to kind of different application.
型錄上之圖片及係數只備參考其尺寸，規格，樣式會因客人所訂購的配件不同而有所改變

康喬工業有限公司 KANG CHYAU INDUSTRY CO., LTD.

247 新北市蘆洲區復興路 227 巷 28 弄 2-10 號
No. 2-10, Aly. 28, Ln. 227, Fuxing Rd., Luzhou Dist., New Taipei City 247, Taiwan
Mail Box: P. O. Box 5-56, Luzhou Dist., New Taipei City 247, Taiwan
Tel: +886-2-22856880~1 Fax: +886-2-22856883
E-mail: kang.chyou@msa.hinet.net Internet: www.kangchyou.com.tw

